



BCS SERIES GALVANIZED STEEL PRODUCT COOLERS
SPECIFICATIONS

200-320 SED (AUG 08)
Page 11

2-FAN UNIT

Model	Face Area (sq ft)	Rows Deep	Surface Area (sq ft)		Coil Volume (cu ft)	Shipping Weight (lb)	
			3 FPI	4 FPI		3 FPI	4 FPI
03006	30.00	6	2,035	2,638	4.2	2,592	2,812
03008	30.00	8	2,714	3,517	5.6	2,999	3,292
03010	30.00	10	3,392	4,397	7.0	3,406	3,772
03406	33.75	6	2,290	2,968	4.7	2,825	3,072
03408	33.75	8	3,053	3,957	6.3	3,269	3,598
03410	33.75	10	3,816	4,946	7.9	3,713	4,124
03606	37.50	6	2,544	3,298	5.3	3,051	3,326
03608	37.50	8	3,393	4,397	7.0	3,530	3,896
03610	37.50	10	4,240	5,496	8.8	4,010	4,467
03806	37.78	6	2,563	3,322	5.3	3,068	3,344
03808	37.78	8	3,418	4,429	7.1	3,549	3,918
03810	37.78	10	4,271	5,537	8.8	4,031	4,492
04206	41.25	6	2,799	3,627	5.8	3,271	3,573
04208	41.25	8	3,732	4,836	7.7	3,784	4,185
04210	41.25	10	4,664	6,046	9.6	4,298	4,801
04306	42.50	6	2,883	3,737	6.0	3,342	3,653
04308	42.50	8	3,845	4,983	7.9	3,867	4,281
04310	42.50	10	4,805	6,229	9.9	4,391	4,910
04406	45.00	6	3,053	3,957	6.3	3,733	4,063
04408	45.00	8	4,071	5,276	8.4	4,280	4,720
04410	45.00	10	5,088	6,595	10.5	4,827	5,376
04606	47.22	6	3,204	4,152	6.6	3,607	3,953
04608	47.22	8	4,272	5,537	8.8	4,174	4,635
04610	47.22	10	5,339	6,921	11.0	4,740	5,316
04806	48.75	6	3,308	4,287	6.8	3,941	4,298
04808	48.75	8	4,410	5,716	9.1	4,521	4,997
04810	48.75	10	5,512	7,145	11.4	5,101	5,695
05206	51.94	6	3,524	4,568	7.3	4,116	4,496
05208	51.94	8	4,699	6,090	9.7	4,722	5,229
05210	51.94	10	5,873	7,613	12.1	5,329	5,963
05406	52.50	6	3,562	4,617	7.4	4,145	4,529
05408	52.50	8	4,750	6,155	9.8	4,757	5,269
05410	52.50	10	5,936	7,694	12.3	5,369	6,009
05706	56.25	6	3,816	4,946	7.9	4,346	4,757
05708	56.25	8	5,089	6,595	10.5	4,989	5,538
05710	56.25	10	6,360	8,244	13.1	5,632	6,318
05606	56.67	6	3,845	4,983	7.9	4,367	4,782
05608	56.67	8	5,126	6,644	10.6	5,014	5,567
05610	56.67	10	6,407	8,305	13.2	5,661	6,352
06206	61.39	6	4,165	5,398	8.6	4,615	5,064
06208	61.39	8	5,554	7,198	11.5	5,300	5,899
06210	61.39	10	6,941	8,997	14.3	5,985	6,734
06606	66.11	6	4,485	5,813	9.3	4,856	5,340
06608	66.11	8	5,981	7,751	12.3	5,580	6,225
06610	66.11	10	7,475	9,689	15.4	6,303	7,109
07006	70.83	6	4,806	6,229	9.9	5,093	5,612
07008	70.83	8	6,408	8,305	13.2	5,854	6,545
07010	70.83	10	8,009	10,381	16.5	6,614	7,478